
A Description-Derived Drug-Drug Interaction Benchmark Reveals Split-Dependent Molecular Representation Rankings

Manel Gil-Sorribes¹ Isaac Filella-Merce¹ Alexis Molina^{1,2}

¹Nostrum Biodiscovery

²AITHYRA

manel.gil@nostrumbiodiscovery.com

alexis.molina@nostrumbiodiscovery.com

Abstract

Drug-drug interaction (DDI) prediction is clinically important and poses a distinct challenge for molecular representation learning. Unlike single-molecule property prediction, DDI requires a predictor to compose two molecular representations into a relational outcome. DrugBank provides curator-authored DDI descriptions rather than ready-made categorical labels, so a categorical prediction target must first be derived from the text. We construct a dataset of DDI pairs by mapping processed descriptions to six text-derived categories and define a benchmark with four holdout regimes that restrict train-test chemical overlap from random pairs to scaffold-disjoint evaluation. We then use this benchmark to compare molecular fingerprints, pretrained sequence representations, and graph-derived features across five seeds and multiple classifier heads. Molecular fingerprints lead the high-overlap random split, whereas graph-derived representations lead the drug- and scaffold-holdout regimes, with the gap increasing as molecular overlap is restricted. Changing the classifier head affects absolute performance but not the relative representation ranking. These results show that representation rankings change with test-set novelty under a fixed description-derived label space.

1 Introduction

Drug-drug interaction (DDI) prediction differs from many molecular property tasks because the prediction target belongs to a pair rather than to an individual molecule. A downstream predictor must combine two molecular representations to infer an interaction that neither single-molecule representation encodes directly. DrugBank provides curator-authored natural-language interaction descriptions at scale [1]. However, turning them into categorical prediction targets is itself a dataset-construction choice.

Evaluation introduces a second choice. Existing DDI studies use pair- and drug-holdout protocols [2], as well as knowledge-graph formulations [3]. Holding out pairs does not necessarily hold out their molecular content: test pairs may still contain training-seen drugs, scaffolds, or closely related structures. Scaffold-aware evaluation addresses this issue [4, 5].

Morgan fingerprints encode fixed local environments [6], MoLFormer and ChemBERTa learn molecular-string representations [7, 8], and graph-derived representations encode molecular connectivity through graph neural networks and message passing [9, 10]. Previous DDI experiments already suggested that fingerprints can be favored when substantial chemical overlap remains [11].

We therefore ask whether a representation ranking persists when the labels are fixed but the molecular novelty of the test population changes.

To evaluate the effects of distinct molecular representations in DDI across different holdout regimes, we construct a dataset of 1,392,791 unordered DrugBank pairs with six text-derived interaction categories. We use dataset to refer to these labeled pairs, and benchmark to refer to the dataset together with the fixed split manifests and evaluation protocol. The benchmark contains random pair, one-drug-unseen, two-drug-unseen, and scaffold-disjoint regimes, allowing the same representation grid to be evaluated as overlap with training is restricted.

We summarize our contributions as:

- a DDI dataset containing 1,392,791 unordered DrugBank pairs and six traceable, description-derived categories,
- a benchmark with four evaluation regimes that explicitly control pair, drug, scaffold, and molecular-similarity overlap, and
- experiments repeated across five model seeds showing that representation rankings change with test-set novelty, while classifier-head complexity has a smaller effect on the conclusions.

2 Dataset construction and benchmark design

2.1 DDI dataset and text-derived labels

Starting from DrugBank DDI records, directed entries are canonicalized to one row per unordered DrugBank ID pair, producing 1,392,791 labeled pairs across 4,437 drugs, with representative description examples provided in Appendix B, Table 7. The subject and affected drug names are then removed from each description to reduce direct identity cues. The cleaned descriptions are embedded with a biomedical SentenceTransformer using a PubMedBERT backbone [12, 13]. Table 1 summarizes molecular-structure coverage in the labeled dataset. The reported split manifests are constructed from the full labeled pair table, with unavailable molecular features handled during feature construction. Additional dataset construction details are provided in Appendix A.

Table 1: Dataset and molecular-structure coverage. The full labeled dataset provides the pair population used to construct the reported split manifests. The structure-resolved subset contains pairs for which both endpoints have valid RDKit-parsable SMILES.

Table or subset	Rows	Pairs	Drugs	Role
Full labeled DDI dataset	1,392,791	1,392,791	4,437	Base for reported split manifests
Pairs with valid SMILES for both drugs	1,158,783	1,158,783	3,468	Fully structure-resolved subset

To derive categorical labels for each drug pair, we clustered the corresponding DDI description embeddings. We first sampled 50,000 descriptions to evaluate alternative clustering configurations. Among the tested agglomerative settings, the six-category solution achieved the strongest combined separation-and-balance score. MiniBatchKMeans was then used for scalable assignment of the complete dataset [14]. Table 2 summarizes the recurring description signals associated with the resulting categories. Full clustering diagnostics and representative wording patterns are provided in Appendix B.

Because the categories remain traceable to recurring DrugBank wording, their content can be inspected against the source descriptions. The text encoder is used to derive the benchmark labels and is not evaluated as a molecular representation for DDI prediction (Figure 1).

We construct the DDI benchmark by combining this fixed label space with four predefined train, validation, and test splits. The labels therefore remain unchanged across evaluation regimes, while the amount and type of molecular information shared between training and test are controlled. This separation is central to the benchmark: differences between splits can be interpreted against the same prediction target rather than against independently constructed DDI datasets.

Table 2: Recurring DrugBank description signals represented by the six text-derived categories. The categories summarize description language rather than expert-adjudicated mechanisms.

Category	Recurring description signals
0	exposure, serum concentration, protein binding, metabolites
1	exposure, efficacy, adverse effects, bioavailability
2	excretion, serum level, efficacy changes
3	CNS effects, blood pressure, coagulation, cardiac effects
4	bleeding, QTc, hypertension, electrolyte and safety effects
5	metabolism and absorption




Figure 1: Benchmark construction and evaluation. DrugBank descriptions are used to obtain the six text-derived labels, while molecular representations are the inference inputs evaluated under pair-, drug-, and scaffold-level holdouts.

2.2 Benchmark regimes and representation evaluation

Four evaluation regimes alter the held-out population while keeping the label space and training protocol fixed. Random pair holdout evaluates unseen combinations while retaining high overlap in the individual drugs. One-drug-unseen evaluation requires exactly one test endpoint to be absent from training, whereas two-drug-unseen evaluation removes both. Scaffold-disjoint evaluation additionally enforces zero train-test DrugBank ID, canonical SMILES, and Bemis-Murcko-framework overlap [5]. ECFP4 similarities [6] are computed with RDKit [15], and the maximum validation/test-to-train Tanimoto similarity is constrained to 0.70. Complete split sizes and overlap checks are reported in Appendix D.

The benchmark evaluates four forms of molecular input that differ in both construction and pre-training signal. Morgan fingerprints are fixed, rule-defined circular descriptors [6]. MolFormer and ChemBERTa use self-supervised molecular-string representations learned with masked-token objectives [7, 8]. GCN features use the Tensor-DTI drug encoder trained on PCBA-1328 [16, 17]. Pair features are concatenated in canonical DrugBank ID order. All four representations are evaluated with the same predefined classifier-head grid and five model seeds to test sensitivity to downstream classifier capacity. Architectural and optimization details are given in Appendix C.

3 What the benchmark reveals

The benchmark reveals a clear representation-ranking reversal as molecular novelty increases: Morgan fingerprints perform best in the high-overlap random split, whereas Tensor-DTI graph-derived features lead the one-drug-unseen, two-drug-unseen, and scaffold-disjoint regimes.

Table 3 quantifies this reversal. The GCN margin over Morgan increases from 0.004 macro-F1 in the one-drug-unseen regime to 0.020 in the two-drug-unseen regime and 0.037 in the scaffold-disjoint regime. Its margin over the strongest non-GCN alternative also increases across these settings, from

Table 3: Representation performance across split regimes. Each cell reports the best observed mean macro-F1 $\pm$ standard deviation across five seeds within the predefined classifier-head grid. Bold marks the leading representation within each regime, and underlining marks the second-best.

Representation	Random	One drug unseen	Two drugs unseen	Scaffold-disjoint
Morgan pair	0.899 $\pm$ 0.000	0.631 $\pm$ 0.002	0.412 $\pm$ 0.003	0.287 $\pm$ 0.005
MoLFormer pair	<u>0.876 $\pm$ 0.001</u>	<u>0.632 $\pm$ 0.001</u>	<u>0.420 $\pm$ 0.005</u>	<u>0.308 $\pm$ 0.005</u>
ChemBERTa pair	0.866 $\pm$ 0.001	0.623 $\pm$ 0.001	0.398 $\pm$ 0.005	0.299 $\pm$ 0.005
GCN pair	0.856 $\pm$ 0.001	0.635 $\pm$ 0.001	0.432 $\pm$ 0.004	0.324 $\pm$ 0.005

0.003 to 0.012 and 0.016, respectively. Within the scaffold-disjoint test set, GCN also outperforms Morgan across similarity bins (Figure 3 in Appendix E). A benchmark restricted to the random split would therefore rank Morgan fingerprints first and obscure the reversal observed under molecular novelty. Because the prediction target, representation grid, and training protocol are held fixed across regimes, the results show that representation rankings depend strongly on the degree of train-test molecular overlap. Additional configuration rankings, paired comparisons, and diagnostic metrics are provided in Appendix E.

Classifier-head variation is smaller than the representation and split effects, and changing the head does not alter the winning representation within any regime.

4 Limitations

The six categories are derived from recurring DrugBank description language rather than expert-adjudicated mechanisms, and may inherit annotation or wording biases from the source. The molecular representations also differ in architecture and pretraining data, so the observed graph-derived advantage cannot be attributed to any one of these factors in isolation.

5 Conclusion

Representation rankings in DDI prediction change substantially with the evaluation regime. We also introduce a description-derived DDI benchmark that combines a fixed six-category label space with pair-, drug-, and scaffold-level holdouts and explicit molecular-similarity controls. Across five seeds, Morgan fingerprints lead under high-overlap random sampling, whereas GCN features lead the one-drug-unseen, two-drug-unseen, and scaffold-disjoint settings. Classifier-head changes affect absolute performance within a representation but do not alter this split-dependent ranking in the evaluated grid.

This work shows that the choice of representation depends on what information is allowed to recur between training and test. Random pair splits primarily evaluate unseen combinations while drug identities and local chemical patterns remain well represented in training. Drug-holdout and scaffold-disjoint settings instead test complementary forms of transfer to unseen compounds and chemical neighborhoods. No single regime is intrinsically correct for every application, but the evaluation split should reflect the intended deployment setting.

These results reinforce the need to compare learned molecular representations against simple fingerprint baselines under explicit overlap controls. Reporting only a random-split score can favor a representation that exploits recurring chemical information while obscuring a different ranking under molecular novelty. Our benchmark provides one way to make these conditions explicit, and DDI benchmarks more generally should report performance together with the degree of drug, scaffold, and molecular-similarity overlap between training and test. Without this context, representation rankings may reflect the evaluation design as much as the transferable information captured by the molecular features.

References

- [1] Craig Knox, Mike Wilson, Christen M. Klinger, Mark Franklin, Eponine Oler, Alex Wilson, Allison Pon, Jordan Cox, Na Eun Chin, Seth A. Strawbridge, et al. DrugBank 6.0: the DrugBank knowledgebase for 2024. *Nucleic Acids Research*, 52(D1):D1265–D1275, 2024. doi: 10.1093/nar/gkad976.
- [2] Yi Zhong, Gaozheng Li, Ji Yang, Houbing Zheng, Yongqiang Yu, Jiheng Zhang, Heng Luo, Biao Wang, and Zuquan Weng. Learning motif-based graphs for drug-drug interaction prediction via local-global self-attention. *Nature Machine Intelligence*, 6:1094–1105, 2024. doi: 10.1038/s42256-024-00888-6.
- [3] Yue Yu, Kexin Huang, Chao Zhang, Lucas M. Glass, Jimeng Sun, and Cao Xiao. SumGNN: multi-typed drug interaction prediction via efficient knowledge graph summarization. *Bioinformatics*, 37(18):2988–2995, 2021. doi: 10.1093/bioinformatics/btab207.
- [4] Zhenqin Wu, Bharath Ramsundar, Evan N. Feinberg, Joseph Gomes, Caleb Geniesse, Aneesh S. Pappu, Karl Leswing, and Vijay Pande. MoleculeNet: a benchmark for molecular machine learning. *Chemical Science*, 9(2):513–530, 2018. doi: 10.1039/C7SC02664A.
- [5] Guy W. Bemis and Mark A. Murcko. The properties of known drugs. 1. molecular frameworks. *Journal of Medicinal Chemistry*, 39(15):2887–2893, 1996. doi: 10.1021/jm9602928.
- [6] David Rogers and Mathew Hahn. Extended-connectivity fingerprints. *Journal of Chemical Information and Modeling*, 50(5):742–754, 2010. doi: 10.1021/ci100050t.
- [7] Jerret Ross, Brian Belgodere, Vijil Chenthamarakshan, Inkit Padhi, Youssef Mroueh, and Payel Das. Large-scale chemical language representations capture molecular structure and properties. *Nature Machine Intelligence*, 4:1256–1264, 2022. doi: 10.1038/s42256-022-00580-7.
- [8] Seyone Chithrananda, Gabriel Grand, and Bharath Ramsundar. ChemBERTa: Large-scale self-supervised pretraining for molecular property prediction. *arXiv preprint arXiv:2010.09885*, 2020. doi: 10.48550/arXiv.2010.09885.
- [9] Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *International Conference on Learning Representations*, 2017. URL <https://openreview.net/forum?id=SJU4ayYgl>.
- [10] Justin Gilmer, Samuel S. Schoenholz, Patrick F. Riley, Oriol Vinyals, and George E. Dahl. Neural message passing for quantum chemistry. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pages 1263–1272. PMLR, 2017.
- [11] Manel Gil-Sorribes and Alexis Molina. Addressing model overcomplexity in drug-drug interaction prediction with molecular fingerprints. *Journal of Cheminformatics*, 18(1):38, 2026. doi: 10.1186/s13321-025-01128-8.
- [12] Yu Gu, Robert Tinn, Hao Cheng, Michael Lucas, Naoto Usuyama, Xiaodong Liu, Tristan Naumann, Jianfeng Gao, and Hoifung Poon. Domain-specific language model pretraining for biomedical natural language processing. *ACM Transactions on Computing for Healthcare*, 3(1): 1–23, 2021. doi: 10.1145/3458754.
- [13] Nils Reimers and Iryna Gurevych. Sentence-BERT: Sentence embeddings using siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing*, pages 3982–3992, Hong Kong, China, 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1410.
- [14] D. Sculley. Web-scale k-means clustering. In *Proceedings of the 19th International Conference on World Wide Web*, WWW ’10, pages 1177–1178, New York, NY, USA, 2010. Association for Computing Machinery. doi: 10.1145/1772690.1772862.
- [15] Greg Landrum, Paolo Tosco, Brian Kelley, et al. RDKit: Release 2024_09_5. Zenodo software release, 2025.

- [16] Manel Gil-Sorribes, Júlia Vilalta-Mor, Isaac Filella-Mercè, Robert Soliva, Álvaro Ciudad, Víctor Guallar, and Alexis Molina. Tensor-DTI: Enhancing biomolecular interaction prediction with contrastive embedding learning. *arXiv preprint arXiv:2601.05792*, 2026. doi: 10.48550/arXiv.2601.05792.
- [17] Sunghwan Kim, Jie Chen, Tiejun Cheng, Asta Gindulyte, Jia He, Siqian He, Qingliang Li, Benjamin A. Shoemaker, Paul A. Thiessen, Bo Yu, Leonid Zaslavsky, Jian Zhang, and Evan E. Bolton. PubChem 2023 update. *Nucleic Acids Research*, 51(D1):D1373–D1380, 2023. doi: 10.1093/nar/gkac956.
- [18] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning*, volume 70, pages 1321–1330. PMLR, 2017.

A Additional dataset construction details

DrugBank interaction records are canonicalized to one row per unordered DrugBank ID pair. Before text embedding, the subject and affected drug names are removed from each interaction description to reduce direct identity cues. The cleaned corpus contains 417 normalized description strings, of which 380 occur in the evaluated dataset.

Among the full labeled pairs, 1,158,783 have valid RDKit-parsable SMILES for both endpoints, corresponding to 3,468 drugs. The reported split manifests, however, are constructed from the full labeled pair table. Pairs containing drugs absent from a molecular feature bank are retained and the unavailable endpoint representation is replaced by a zero vector during feature construction. DrugBank source data remain subject to the applicable license. Benchmark scripts, aggregate artifacts, and manuscript resources will be released separately.

B Text clustering and label interpretation

Cleaned descriptions are embedded with the SentenceTransformer checkpoint pritamdeka/S-PubMedBert-MS-MARCO¹, which uses a PubMedBERT backbone within the Sentence-BERT framework [12, 13]. Candidate cluster counts are evaluated on a sample of 50,000 description embeddings before scalable assignment over the full table. The combined selection score is

$$\text{selection score} = \text{silhouette} - \text{Davies-Bouldin} + \text{cluster size balance},$$

where cluster-size balance is the minimum cluster size divided by the maximum cluster size. Calinski-Harabasz is reported separately as an additional diagnostic and is not included in the combined score.

Table 4 compares the sampled candidate granularities. Agglomerative clustering with $k = 6$ has the strongest listed combined score. MiniBatchKMeans [14] is then used to assign the full corpus at the selected six-category granularity, which is a practical benchmark choice rather than a mathematically unique optimum.

Table 4: Cluster-granularity diagnostics on a sample of 50,000 SentenceTransformer description embeddings. The combined selection score is silhouette minus Davies-Bouldin plus cluster-size balance. Calinski-Harabasz is reported but not included in the score. Agglomerative clustering with $k = 6$ has the strongest listed score and motivates the six-category label granularity used for full-corpus assignment.

Method	k	Sil.	Davies-Bouldin	Calinski-Harabasz	Balance	Score
Agglomerative	6	0.565	1.205	19,135	0.719	0.079
Agglomerative	8	0.644	1.045	20,807	0.253	-0.148
Agglomerative	50	0.943	1.095	34,605	0.003	-0.148
Agglomerative	30	0.892	1.112	24,878	0.020	-0.199
Agglomerative	5	0.506	1.184	18,390	0.386	-0.292

Benchmark prevalence is frequency-weighted because some cleaned templates recur many times. Figure 2 and Table 5 therefore report both pair-weighted prevalence and unique-template counts.

Clusters 0, 1, 2, and 5 are dominated by a small number of recurring templates, whereas clusters 3 and 4 contain greater template diversity. Reporting both pair-weighted counts and unique-template counts makes this difference visible.

Tables 6 and 7 provide description-level interpretability aids. They summarize recurring wording patterns used by the benchmark target. They are not an external biological validation.

The categories can be traced to recurring wording in the source descriptions, but should not be interpreted as independently adjudicated mechanistic or clinical labels.

¹<https://huggingface.co/pritamdeka/S-PubMedBert-MS-MARCO>




Figure 2: Cluster-size distribution for the six text-derived interaction-description categories.

Table 5: Cluster statistics for the benchmark table used in model evaluation. Pair percentages are frequency-weighted by benchmark rows, whereas template counts treat normalized descriptions as unique strings.

Cluster	Pairs	Pair %	Cleaned templates	Top-5 template row %
0	60,169	4.3	23	99.8
1	423,895	30.4	37	99.8
2	230,493	16.5	17	99.9
3	215,150	15.4	104	69.3
4	250,567	18.0	182	54.7
5	212,517	15.3	18	100.0

Table 6: Textual summary of the six text-derived interaction-description categories. The summaries link each benchmark label to recurring DrugBank wording patterns and provide a qualitative view of label interpretability.

Cluster	Description-level summary	Representative signals
0	pharmacokinetic exposure changes, metabolic inhibition or induction, protein binding and distribution, therapeutic effect modulation	serum, concentration, protein, binding, active, metabolites, metabolite
1	pharmacokinetic exposure changes, pharmacodynamic toxicity additivity, therapeutic effect modulation	effects, adverse, risk, severity, therapeutic, efficacy, bioavailability
2	pharmacokinetic exposure changes, therapeutic effect modulation	level, excretion, serum, efficacy, reduction
3	therapeutic effect modulation, cardiac electrophysiology, central nervous system depression, blood pressure and vascular tone, coagulation and bleeding, glucose regulation	depressant, activities, nervous, central, cns, antihypertensive, hypotensive, arrhythmogenic
4	pharmacodynamic toxicity additivity, cardiac electrophysiology, blood pressure and vascular tone, coagulation and bleeding, renal and electrolyte safety, glucose regulation	severity, risk, hypertension, bleeding, prolongation, qtc, hyperkalemia, hemorrhage
5	pharmacokinetic exposure changes, metabolic inhibition or induction, therapeutic effect modulation	metabolism, absorption

Table 7: Representative wording patterns for the text-derived labels. These template-like patterns are extracted from frequent cleaned descriptions with drug names omitted and show recurring interaction-description language.

Cluster	Representative description patterns
0	serum concentration can be increased when combined, protein binding and active-metabolite language
1	therapeutic efficacy can be decreased when used in combination, therapeutic efficacy can be increased when used in combination
2	excretion rate can be decreased, resulting in higher serum level, serum-level and excretion language
3	anticoagulant activities can be increased, central nervous system depressant activities can be increased
4	risk or severity of bleeding can be increased, risk or severity of hypertension can be increased
5	metabolism can be increased when combined, metabolism can be decreased when combined

C Molecular representations and model heads

This section separates molecular representation choice, pair construction, classifier-head capacity, and the common training protocol. Morgan fingerprints use radius 2 and 2048 bits, MoLFormer uses `ibm/MoLFormer-XL-both-10pct`, ChemBERTa uses `DeepChem/ChemBERTa-77M-MLM`, and GCN features use the Tensor-DTI drug encoder trained on PCBA-1328 [16, 17]. All pair features concatenate endpoint vectors in canonical DrugBank ID order.

Table 8 gives the model-head and optimization settings. The auxiliary-regression head uses a description embedding only as a training-time target. Interaction text is not an inference-time model input. Its purpose is to regularize the molecular pair representation toward the text-derived label space.

Table 8: Model-head and training hyperparameters used in the final streaming Torch experiments. Values are taken from the training script used for the benchmark grid.

Component	Setting
Linear head	Single linear layer from input features to six classes
MLP head	512-unit hidden layer, ReLU, dropout 0.2, 256-unit hidden layer, ReLU, dropout 0.2, six-class output
Residual MLP	512-dimensional projection followed by two residual blocks, each block uses linear-ReLU-dropout 0.2-linear with layer normalization
Gated MLP	512-dimensional value branch multiplied by a 512-dimensional sigmoid gate, followed by dropout 0.2, 256-unit hidden layer, dropout 0.2, and output layer
Feature-attention MLP	512-dimensional value branch multiplied by a learned sigmoid feature-attention vector, followed by the same 256-unit head as the gated MLP
Pair-attention head	Two drug vectors projected to 256 dimensions, four-head self-attention with dropout 0.1 over the two tokens, layer-normalized 512-dimensional flattened token output passed to a 512-unit head with dropout 0.2
Auxiliary-regression head	512-unit and 256-unit encoder with dropout 0.2, cross-entropy classifier plus 768-dimensional regression head trained with cosine embedding loss, $\lambda_{\text{cls}} = 1.0$, $\lambda_{\text{reg}} = 1.0$
Optimization	AdamW, learning rate 10^{-3} , weight decay 10^{-4} , 30 epochs, batch size 1024, evaluation batch size 8192
Data handling	Streaming feature construction, train-set feature standardization applied to held-out batches, final Torch runs use all rows assigned to each split, the extended comparison additionally includes eight shallow baseline configurations. Drugs absent from a representation feature bank are assigned zero vectors.
Seeds	Data construction seed 42, model seeds 11, 22, 33, 44, and 55 for the Torch grid

The shared representation and optimization controls help attribute performance differences to the representation, split regime, and head choices recorded in the result tables. Data construction uses seed 42, and model results are aggregated over seeds 11, 22, 33, 44, and 55. Endpoint vectors use canonical DrugBank ID order, and feature standardization is fit on the training partition only.

D Split construction and validation

The four regimes isolate complementary forms of generalization. Random evaluation tests unseen pair combinations while retaining high individual-drug overlap. One-drug-unseen and two-drug-unseen evaluation require one or both held-out endpoints, respectively. Scaffold-disjoint evaluation restricts drug identity, canonical SMILES, Bemis-Murcko scaffold, and molecular-similarity overlap. These regimes should therefore be read as complementary generalization tests rather than as a single strictly monotonic difficulty scale.

Table 9 reports the resulting sample counts. Random evaluation uses the full benchmark, whereas the drug-holdout regimes retain rows satisfying their endpoint-assignment constraints. Scaffold-disjoint evaluation retains within-partition pairs and removes cross-partition pairs.

Table 9: Dataset split sizes for the DrugBank-pair benchmark. Random, one-drug-unseen, and two-drug-unseen splits are drawn from the 1,392,791-row labeled dataset. Scaffold-disjoint evaluation starts from the same base. It retains within-partition pairs and removes cross-partition pairs.

Split	Train	Validation	Test	Evaluated rows
Random	974,954	139,279	278,558	1,392,791
One drug unseen	675,377	191,699	397,605	1,264,681
Two drugs unseen	691,248	13,179	54,956	759,383
Scaffold-disjoint	806,341	10,970	36,621	853,932

All 47,591 scaffold-disjoint validation and test pairs have valid molecular structures for both endpoints. Of the 806,341 training pairs, 613,853 have two valid structures, while 192,488 contain at least one unavailable or invalid structure and are retained using the zero-vector feature fallback described in Appendix C.

One-drug-unseen has the largest test set because many pairs satisfy its one-held-out-endpoint rule. The smaller scaffold-disjoint validation and test sets follow from the globally consistent molecular partition and cross-partition exclusions, rather than from arbitrary subsampling. Table 10 records the overlap and assignment checks.

Table 10: Split-validation checks for the split suite. Train-test pair overlap is zero in every setting. The scaffold-disjoint split additionally has zero train-test DrugBank ID, canonical SMILES, and Bemis-Murcko scaffold overlap. Its maximum validation/test-to-train ECFP4 Tanimoto similarity is 0.70, with no value above the threshold.

Split	Pair overlap	Train-test drug overlap	Validation check
Random	0	4,169/4,207	row-level shuffle, most test drugs remain training-seen
One drug unseen	0	2,995/3,874	0 rows violate the one-unseen-drug rule
Two drugs unseen	0	0/862	0 rows violate the two-unseen-drug rule
Scaffold-disjoint	0	0/656	0 canonical SMILES/scaffold overlap, maximum ECFP4 Tanimoto 0.70

Every regime has zero train-test unordered-pair overlap. The scaffold-disjoint split additionally has zero train-test DrugBank ID overlap and, among structure-resolved compounds, zero canonical SMILES and Bemis-Murcko scaffold overlap. The molecular-similarity constraint is verified in Table 10. These controls test chemical-neighborhood generalization on a different axis from the endpoint novelty isolated by two-drug-unseen evaluation.

E Extended results

The following subsections retain the configuration-level evidence behind the main-paper winner statements. They distinguish representation effects from classifier-head variation and report complementary probability-based metrics without changing macro-F1 as the primary ranking metric.

E.1 Top-performing configurations

Table 11 reports the top three five-seed Torch configurations within each split, selecting representation and head separately for each regime. It supports the winner statements in the main text.

Table 11: Top three five-seed Torch configurations per evaluated split. Morgan pair features lead random evaluation, whereas GCN pair features lead all three drug- and scaffold-holdout settings. The scaffold-disjoint setting is also the only leading setting in which pair attention outperforms the residual MLP for the same representation.

Split	Rank	Configuration	Runs	Accuracy	Macro-F1
Random	1	Morgan pair + Aux. reg. MLP	5	0.905 ± 0.000	0.899 ± 0.000
	2	Morgan pair + MLP	5	0.902 ± 0.001	0.897 ± 0.001
	3	Morgan pair + Residual MLP	5	0.902 ± 0.000	0.896 ± 0.001
One drug unseen	1	GCN pair + Residual MLP	5	0.672 ± 0.001	0.635 ± 0.001
	2	MoLFormer pair + Residual MLP	5	0.669 ± 0.001	0.632 ± 0.001
	3	Morgan pair + Residual MLP	5	0.669 ± 0.003	0.631 ± 0.002
Two drugs unseen	1	GCN pair + Residual MLP	5	0.496 ± 0.005	0.432 ± 0.004
	2	GCN pair + MLP	5	0.507 ± 0.004	0.432 ± 0.007
	3	GCN pair + Aux. reg. MLP	5	0.496 ± 0.002	0.426 ± 0.002
Scaffold-disjoint	1	GCN pair + Pair attention	5	0.343 ± 0.006	0.324 ± 0.005
	2	GCN pair + MLP	5	0.345 ± 0.004	0.319 ± 0.009
	3	GCN pair + Aux. reg. MLP	5	0.336 ± 0.004	0.319 ± 0.004

Morgan occupies the top random positions, whereas GCN leads one-drug-unseen, two-drug-unseen, and scaffold-disjoint evaluation. Pair attention gives the highest observed scaffold-disjoint GCN result.

E.2 Paired representation and head comparisons

Differences in Table 12 are computed seed-wise with the same five model seeds, so the intervals describe paired configuration margins rather than independent-run comparisons.

Table 12: Paired five-seed macro-F1 differences for key benchmark comparisons. Differences are computed seed-wise as the first configuration minus the second. Intervals are 95% paired t -intervals over seeds 11, 22, 33, 44, and 55.

Comparison	Contrast	Split	Difference
Random top configuration	Morgan aux. regression vs Morgan MLP	Random	0.002 [0.001, 0.004]
One-drug representation margin	GCN residual vs MoLFormer residual	One drug unseen	0.004 [0.002, 0.005]
Two-drug representation margin	GCN residual vs MoLFormer residual	Two drugs unseen	0.012 [0.004, 0.020]
Scaffold representation margin	GCN pair attention vs MoLFormer residual	Scaffold-disjoint	0.015 [0.009, 0.022]
Scaffold head margin	GCN pair attention vs GCN residual	Scaffold-disjoint	0.009 [-0.002, 0.020]

The GCN-MoLFormer margin is small but positive for one-drug-unseen evaluation and larger for two-drug-unseen evaluation. The listed GCN configuration exceeds the listed MoLFormer configuration in scaffold-disjoint evaluation because its paired interval excludes zero. By contrast, the pair-attention versus residual-GCN interval includes zero, so head superiority is not conclusive.

E.3 Probability-based diagnostics

Alongside macro-F1, Table 13 reports balanced accuracy, MCC, macro AUROC, macro AUPRC, and confidence ECE [18] for the leading configuration in each regime. These metrics assess complementary aspects of class-balanced discrimination and confidence calibration. ECE is not a full epistemic-uncertainty analysis.

Table 13: Probability-based diagnostics for the leading five-seed configuration in each evaluated split. AUROC and AUPRC are macro-averaged one-vs-rest multiclass metrics recomputed from archived prediction probabilities. ECE is a 15-bin confidence calibration error.

Split	Configuration	Bal. acc.	MCC	AUROC	AUPRC / ECE
Random	Morgan pair + auxiliary-regression MLP	0.888 ± 0.001	0.875 ± 0.000	0.991 ± 0.000	$0.964 \pm 0.000 / 0.019 \pm 0.001$
One drug unseen	GCN pair + residual MLP	0.624 ± 0.003	0.563 ± 0.001	0.887 ± 0.001	$0.670 \pm 0.002 / 0.171 \pm 0.003$
Two drugs unseen	GCN pair + residual MLP	0.419 ± 0.003	0.330 ± 0.007	0.758 ± 0.001	$0.415 \pm 0.006 / 0.318 \pm 0.003$
Scaffold-disjoint	GCN pair + pair attention	0.325 ± 0.004	0.192 ± 0.007	0.689 ± 0.005	$0.310 \pm 0.005 / 0.322 \pm 0.005$

Discrimination and calibration both degrade under stricter generalization. The strong random result is not preserved under unseen-drug and scaffold-disjoint evaluation, while macro-F1 remains the primary metric for comparing the imbalanced six-category task.

E.4 Comparison of generalization regimes

Each row in Table 14 compares the same training setup, representation, and head across two-drug-unseen and scaffold-disjoint evaluation. Because the evaluated pair populations differ, the comparison is descriptive rather than a paired test on identical examples.

Table 14: Matched comparison between two-drug-unseen and scaffold-disjoint evaluation. Each row compares the same training setup, molecular representation, and model head across splits. Positive Δ indicates higher scaffold-disjoint macro-F1. Negative Δ indicates higher two-drug-unseen macro-F1.

Matched group	Settings	Scaffold higher	Mean Δ	Median Δ
All matched appendix settings	36	0	-0.085	-0.093
Torch settings	28	0	-0.093	-0.098
Morgan pair settings	9	0	-0.100	-0.122
GCN pair settings	9	0	-0.082	-0.098
Torch Morgan pair settings	7	0	-0.110	-0.124
Torch GCN pair settings	7	0	-0.091	-0.106

Scaffold-disjoint macro-F1 is lower in all 36 matched comparisons. This supports treating it as a distinct chemical-generalization stress test rather than another drug-holdout split.

E.5 Scaffold-disjoint performance by training-set similarity

To examine performance within the scaffold-disjoint test population, we stratify test pairs by their proximity to the training chemistry. For each endpoint, we compute its maximum ECFP4 Tanimoto similarity to any structure-resolved training molecule and define the pair-level similarity as the larger of the two endpoint values. Lower values therefore indicate that both molecules in the pair are distant from the training set.




Figure 3: Performance within the scaffold-disjoint test set as a function of similarity to the training chemistry. Left: number of test pairs in each bin of maximum endpoint-to-training ECFP4 Tanimoto similarity. Right: five-seed macro-F1 for the Morgan residual-MLP and GCN pair-attention configurations. Error bars show mean $\pm$ standard deviation across five model seeds. The lowest populated similarity bin contains only nine pairs and should therefore not be interpreted quantitatively.

E.6 Classifier-head summary

Table 15 averages over representations and therefore provides a supporting view of head robustness rather than a replacement for representation-specific comparisons.

Table 15: Classifier-head summary from the complete evaluated configuration set. Values average the five-seed means over the four pair representations within each split, so they are intended as supporting head-level evidence rather than a replacement for representation-specific comparisons.

Split	Rank	Head	Mean accuracy	Mean macro-F1
Random	1	Residual MLP	0.880	0.874
	2	Feature attention	0.869	0.861
	3	Gated MLP	0.868	0.860
	4	Aux. reg. MLP	0.863	0.854
One drug unseen	1	Residual MLP	0.668	0.630
	2	Gated MLP	0.663	0.619
	3	Feature attention	0.660	0.616
	4	Aux. reg. MLP	0.654	0.613
Two drugs unseen	1	Residual MLP	0.478	0.416
	2	Gated MLP	0.475	0.401
	3	Aux. reg. MLP	0.465	0.398
	4	MLP	0.470	0.398
Scaffold-disjoint	1	Residual MLP	0.321	0.302
	2	MLP	0.314	0.293
	3	Feature attention	0.315	0.293
	4	Aux. reg. MLP	0.313	0.293

Residual MLP is the most consistently strong average head. This does not contradict pair attention producing the single best scaffold-disjoint GCN configuration, because head-level averages should not replace representation-specific comparisons.